



MimioTeach



DESCRIPTION

The MimioTeach™ interactive system transforms any dry erase board into a fully interactive whiteboard. The patented infrared and ultrasound sensor technology fits neatly into a small, unobtrusive bar that attaches easily to a board. Combine it with a projector and computer, and it becomes a fully interactive system. Lightweight yet durable, the MimioTeach system is easy to handle and transport. Powerful MimioStudio™ software drives the system and dramatically expands teaching options.

PACKAGE CONTENTS

MimioTeach bar with embedded wireless interface, rechargeable stylus, MimioHub™ wireless receiver, USB micro-B cable (5 m/16 ft), magnetic mounting bracket, 5V 500 mA USB power supply, 1 DVD containing Windows (MimioStudio 7) in 26 languages (English, French, Italian, German, Spanish, Russian, Dutch, Simplified Chinese, Traditional Chinese, Japanese, Korean Hangul, Arabic, Hindi, Turkish, Hungarian, Bahasa Indonesian, Greek, Croatian, Swedish, Danish, Vietnamese, Bahasa Malay, Polish and Hebrew). Portuguese installers will be made available from Distributors in Brazil and Portugal.

SPECIFICATIONS

Operating Systems Supported

Windows XP SP2, Vista, Windows 7.

System Requirements

Windows compatible PC with Pentium II 750 MHz+ processor or equivalent.
512 MB RAM minimum (1 GB RAM recommended).
400 MB free disk space minimum.
DVD ROM Drive.
Available USB port.

Software

MimioStudio 7 for Windows. MimioStudio 7 for Mac and Linux will be released at a later date.

Computer Interface

USB (USB 2.0 compliant).
USB Cable—"micro-B" USB connector.
MimioHub will connect via USB to the PC.

Data Transfer Rate—USB

Full-speed USB (12 Mbps).

Power Consumption

Connected to computer via USB—0,5 W.
Stand-alone with AC Adapter 110 V—0,75 W.
Stand-alone with AC Adapter 220 V—0,9 W.

MimioTeach Bar Dimensions

375,4 mm H x 68 mm W x 38 mm D (14.8 in. H x 2.7 in. W x 1.5 in. D)

Weight

Bar: 305 g (10.75 oz)
Stylus: 30 g (1 oz)
Bar and Stylus: 335 g (11.82 oz)

Whiteboard Active Area (per device)

Interactive mode with projector supports 2 m x 2,4 m (6.6 ft x 7.9 ft.), up to 3 m (10 ft.) standard aspect ratio diagonal projection display and 2,9 m (9.4 ft.) diagonal in wide screen mode.



MimioTeach

SPECIFICATIONS

Stylus	<p>Ergonomically elegant stylus for interactive use.</p> <p>Ultrasound at 40 kHz (frequency) + Infrared at 940 nm/sec (wavelength).</p> <p>Uses single 3,7 V Lithium-Ion rechargeable cell with 70 mAh capacity.</p> <p>Stylus recharges when docked in cradle on left side of MimioTeach. Retains a charge for 8 – 10 hours.</p> <p>Full recharge in 3 hours.</p> <p>60-second safety shut-off.</p> <p>Two buttons on the stylus activate functions: Right Click and MimioStudio Tools.</p> <p>Solid Teflon stylus with replaceable tip ensures ultra-smooth action on all board or screen surfaces.</p>
Resolution & Tracking Speed	<p>Signal tracking frequency 87 times per second.</p> <p>Signal tracking speed 2,7 m (9 ft) per second.</p> <p>4.800 x 9.600 line effective resolution on 1,2 m x 2,4 m (4 ft x 8 ft) board.</p>
Positioning	<p>MimioTeach bar should be mounted on the left side of the whiteboard in a location outside the projection area. Sensors must face a projected surface that is within the maximum Active Area range of the device.</p>
Controls & Indicators at the Whiteboard	<p>2 push-button functions on the MimioTeach bar: Interactive mode and Calibrate/Re-calibrate.</p> <p>1 Indicator: Link.</p>
Temperature	<p>Operating: 0°C to 30°C (32°F to 86°F).</p> <p>Storage: -20°C to 55°C (-4°F to 131°F).</p>
Humidity	<p>Operating: 15% to 75% non-condensing.</p> <p>Storage: 0% to 90% non-condensing.</p>
Wireless Connectivity	<p>Enables a dedicated 2,4 GHz bidirectional point-to-point wireless connection to the computer through MimioHub, a USB “thumb drive” receiver with maximum range of 10 m (30 ft).</p> <p>Does not require Bluetooth, special card, wireless networks or wireless PC.</p> <p>MimioHub is a standard USB device using HID drivers and comes paired with MimioTeach.</p> <p>MimioHub can dock in the back slot of the MimioTeach bar when not in use.</p>
Wireless Data Transfer Rate	<p>250 Kbps</p>
Certification & Compliance	<p>Wireless: FCC, IC, CE (Additional Countries Pending).</p> <p>Safety: UL/CSA/EN/IEC 60950-1 (CE & TUV NRTL) (Additional Countries Pending).</p> <p>EMC: FCC, IC, CE.</p> <p>Class B (Additional Countries Pending).</p> <p>Environmental: RoHS, WEEE, REACH compliant.</p>
International Use	<p>Computer USB or batteries as primary power source enable “Start up and Go” in any country.</p> <p>International USB and AC Adapter for AC-powered use.</p>
Product Warranty	<p>2 years, extended to 5 years on all hardware components except batteries, with online registration.</p> <p>Unlimited lifetime warranty on software. Battery warranty is one year from the date of shipment.</p> <p>Defective battery will be replaced when proven to be due to manufacturing process, rather than customer abuse or misuse.</p>
Other Accessories Available	<p>USB extension cable, AAA batteries for MimioTeach battery operation, metallic mounting brackets w/removable adhesive strips for non-metallic surfaces, stylus, replaceable Lithium-Ion battery for stylus, North American or International AC adapters.</p>
